Outline Dimension



LED BKL

EL BKL or without BKL

Feature

1. 5X8 dots with cursor
2. Built-in controller (KS0066U or Equivalent)
3. +5V power supply(Also available for +3.0V)
4. 1/16 duty cycle
5. BKL to be driven by pin1,pin2,or A,K

Interface pin connections

PIN NO	Symbol	Function
1	VDD	Power supply
2	VSS	Power supply
3	V0	Contrast adjustment
4	RS	H/L Register select signal
5	R/W	H/L Read/Write signal
6	E	H/L Enable signal
7	DB0	H/L Data bus line
8	DB1	H/L Data bus line
9	DB2	H/L Data bus line
10	DB3	H/L Data bus line
11	DB4	H/L Data bus line
12	DB5	H/L Data bus line
13	DB6	H/L Data bus line
14	DB7	H/L Data bus line
15	A	+4.2V for BKL
16	K	Power supply for BKL(0V)

Mechanical Data

Item	Standard	Unit
Module dimension	85.0x29.5	mm
Viewing area	64.5x16.4	mm
Dot size	0.56x0.61	mm
Character size	3.00x5.23	mm

Absolute Maximum Rating

Item	Symbol	Standard			Unit
		Min	Typ	Max	
Power supply	VDD-VSS	-0.3	--------	5.5	V
Input voltage	VI	-0.3	--------	VDD	

Electronical characteristics

Item	Symbol	Condition	Standard			Unit
			Min	Typ	Max	
Input voltage	VDD	+5V	4.7	5.0	5.5	V
		+3.3V	2.7	3.0	5.3	V
Supply current	IDD	VDD=5V	------	1.5	4	mA
Recommended LCD driving voltage for normal temp version module	VDD-V0	-20°C	------	------	------	V
		0 °C	4.7	5.0	5.5	
		25°C	4.3	4.5	4.7	
		50°C	4.1	4.3	4.5	
		70°C	------	-------	------	
LED forward voltage	VF	25°C	------	4.2	4.6	V
LED forward current	IF	25°C	------	120	------	mA
EL power supply current	IEL	VEL=110V AC 400Hz	-----	-------	------	mA

Display character address code

Display position

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
DDRAM address	00	01	02	---	---	---	---	---	---	---							0FH
DDRAM address	40	41	42	---	---	---	---	---	---	---							4FH