


Outline Dimension



Feature

1. 5X8 dots with cursor
2. Built-in controller (KS0066U or Equivalent)
3. +5V power supply
4. 1/16 duty cycle
5. BKL to be driven by pin15,pin16.

Mechanical Data

Item	Standard	Unit
Module dimension	98.0x60.0X18.6	mm
Viewing area	76.0x26.0	mm
Dot size	0.55x0.55	mm
Character size	2.95x4.75	mm

Interface pin connections

PIN NO	Symbol	Function
1	VSS	GND
2	VDD	+5V
3	V0	Contrast adjustment
4	RS	H/L Register select signal
5	R/W	H/L Read/Write signal
6	E	H/L Enable signal
7	DB0	H/L Data bus line
8	DB1	H/L Data bus line
9	DB2	H/L Data bus line
10	DB3	H/L Data bus line
11	DB4	H/L Data bus line
12	DB5	H/L Data bus line
13	DB6	H/L Data bus line
14	DB7	H/L Data bus line
15	A	+3.8V for BKL
16	K	Power supply for BKL(0V)

Absolute Maximum Rating

Item	Symbol	Standard			Unit
		Min	Typ	Max	
Power supply	VDD-VSS	-0.3	-----	5.5	V
Input voltage	VI	-0.3	-----	VDD	

Electronical characteristics

Item	Symbol	Condition	Standard			Unit
			Min	Typ	Max	
Input voltage	VDD	+5V	4.7	5.0	5.5	V
		+3.3V	2.7	2.0	5.3	
Supply current	I _{DD}	VDD=5V	-----	3.0	3.5	mA
Recommended LCD driving voltage for normal temp version module	VDD-V0	-20°C	-----	-----	-----	V
		0 °C	4.7	5.0	5.5	
		25°C	4.3	4.5	4.7	
		50°C	4.1	4.3	4.5	
		70°C	-----	-----	-----	
LED forward voltage	V _F	25°C	-----	3.8	4.0	V
LED forward current	I _F	25°C	-----	55	-----	mA
EL power supply current	I _{EL}	V _{EL} =110V AC 400Hz	-----	-----	-----	mA

Display character address code

Display position		1	2	3	---	---	---	---	---	19	20
DDRAM address	00 01 02	---	---	---	---	---	---	---	---	12H	13H
DDRAM address	40 41 42	---	---	---	---	---	---	---	---	52H	53H
DDRAM address	14 15 16	---	---	---	---	---	---	---	---	26H	27H
DDRAM address	54 55 56	---	---	---	---	---	---	---	---	66H	67H